

The technical content of this document is approved under the authority of DOA ref. EASA.21J.140 (C764 Iss. 1)

7.58 BASKET WITH REMOVABLE FABRIC SIDE PANEL

7.58.1 GENERAL

This supplement shall be inserted in the Maintenance Manual, in Section 7: 'Supplements' with the revisions record sheet amended accordingly.

Information contained herein supplements, or in the case of conflict, supersedes that contained in the basic Maintenance Manual. For Limitations, Procedures, and Performance Data not contained in this supplement, consult the basic Hot Air Balloon Maintenance Manual.

Issue 1 of this supplement consists of 1 page.

7.58.2 ENVELOPE REPAIRS

No Change.

7.58.3 BASKET REPAIRS

7.58.3.1 Routine Maintenance

Fasteners and cross-tapes should be visually inspected before every flight for damage, wear or distortion.

7.58.4 FUEL SYSTEM REPAIRS

No change.

7.58.5 INSTRUMENT REPAIRS

No change.

7.58.6 MAINTENANCE SCHEDULE

Basket Type:			
Part No.:		Serial No.:	

7.58.6.5.8 Basket (additional)

Component	Check / Inspect / Record	Pass/Fail (✓)/(x)
Trim	Check conditions/ present	
Cross-tapes	Check condition	
Quick Release Buckles	Check condition	
Velcro	Check condition/ Bond is satisfactory	
Cordura	Check condition	

7.58.6.6.5 Baskets (additional)

The removable side panel is primarily used for basket side access of fuel cylinders, however, it is essential that the cross-bracing tapes and quick release hardware are checked for security and damage at the annual 100 hr/Annual inspection. Further checks to the Velcro contacts are recommended for overall completeness of the side panel assembly inspection.

Workpack No.	CN	Inspection Date	Inspectors Signature/No.
---------------------	----	------------------------	---------------------------------